

Partners

The project is conducted in close collaboration with key industrial partners, including two **waste-to-energy plants**, a **paper mill**, a **lime plant**, and a **cement plant**, which will test the CARMEN pilot unit one after another.

avea

JASS
for people and nature

Lhoist

SWB
Verwertung

Portlandzementwerk
Wittekind
Hugo Miesbach Söhne KG

TECHNISCHE
UNIVERSITÄT
DARMSTADT

TU Darmstadt, as project leader, is building the pilot plant and operates it together with the site operators. It will then design a larger CaL demonstration plant.

Technology
Arts Sciences
TH Köln

TH Köln assesses the sustainability and economic performance of the process for different industries.

MERCK

Merck KGaA contributes financially to evaluate the applicability of results to the pharmaceutical and chemical sectors.

House
of Energy

House of Energy organizes events, manages public outreach, and has initiated an advisory board to ensure knowledge transfer and practical relevance.

Contact

Energy Systems and Technology (EST)
Technical University of Darmstadt

Prof. Dr.-Ing. Bernd Eppe

bernd.eppe@est.tu-darmstadt.de

+49 6151 16 23001

Dr.-Ing. Jochen Ströhle

jochen.stroehle@est.tu-darmstadt.de

+49 6151 16 23003

Matti Löhden

matti.loehden@est.tu-darmstadt.de

+49 6151 16 22693

Robin Suardi


robin.suardi@est.tu-darmstadt.de

+49 6151 16 22676



Website

www.carbonate-looping-carmen.de



CARMEN – Carbonate Looping with a mobile pilot plant

Supported by:



Federal Ministry
for Economic Affairs
and Energy

on the basis of a decision
by the German Bundestag

Project

In the CARMEN project, the innovative Carbonate Looping (CaL) process for CO₂ capture from flue gases is being demonstrated under real industrial conditions. A mobile pilot plant is built and operated at five energy-intensive industrial sites. The project aims to reduce industrial CO₂ capture costs and to accelerate decarbonization. CARMEN is a joint project with ten partners led by TU Darmstadt.

Process

In the CaL process, CO₂ is efficiently absorbed from flue gases. This post-combustion method uses lime for CO₂ separation. The CaL-process consists of two connected fluidized bed reactors, the carbonator and the calciner, in which the lime circulates and binds the CO₂. As a result, a CO₂-free flue gas stream and a pure CO₂ stream leave the CaL process.

Advantages

A key advantage of the CaL process is its ability to efficiently recover high-temperature heat, boosting the thermal plant's overall efficiency. In addition, CaL can be retrofitted to existing industrial plants without the need for complex flue gas pre-treatment.

Key Questions

For each industrial site, the following questions are addressed:

- ? What are the optimal operating conditions of the CaL unit under the site-specific conditions?
- ? Which CO₂ capture rate is technically feasible and economically viable?
- ? How can the CaL excess heat be best utilized?
- ? How can the captured CO₂ be used?
- ? How can the CaO sorbent be best managed?
- ? How economical is the process for a demo or industrial plant?

